








CAD FILE:



P.C.B. LAYOUT



SCHEMATIC (NON-SHORTING)

MODEL NO.	KNOB(G)
T4-124701-G	(2~10)mm



SPECIFICATIONS

Rating	AC250V 3A
CIRCUIT	1P2T
Insulation Resistance	> 100 MΩ
Travel	2.8mm
Contact Resistance	< 100 mΩ
Operating Force	300gf ± 100gf
Operating Life	10,000 cycles

8					TOLERANCE UNLESS SPECIFIED WITHIN 1.5mm :±0.1mm OVER 1.5mm : ±0.2mm	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DONGGUAN TIANDU ELECTRONICS CO.,LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF DONGGUAN TIANDU ELECTRONICS CO., LTD				
7	STEEL BALL	STEEL	1	NATURAL						
6	SPRING	STEEL WIRE	1	NATURAL						
5	CONTACT CLIP	BRASS STRIP	1	Ag PLATED			DESCRIPTIONS OF REVISION			APPD.
4	TERMINAL	BRASS STRIP	3	Ag PLATED	TITLE : VERTICAL SLIDE SWITCH		UNIT : mm	DRWG NO.: CMTDDZ-T4-124701-00		
3	CASE	PA66	1	BLACK	MODEL: T4-124701-G		SCALE: 3:1	DWN.	ERIC	2013-6-17
2	COVER	SUS	1	NATURAL	CMTDDZ 东莞市田都电子有限公司 DONGGUAN TIANDU ELECTRONICS CO.,LTD.			CHK'D	MAIKO	2013-6-17
1	KNOB	PA66	1	BLACK				APPD.	Coco	2013-6-17
NO.	PARTS	MATERIALS	Q'TY	FINISH						