

1

2

3

4

5

文件类型:

产品图面

REV.	ECN NO.	DESCRIPTION	DRWN	APPD.	DATE.

Specifications:

Electrical:

- Current Rating
1.5A/contact terminal
- Voltage Rating
30V DC
- Contact Resistance
30 milliohms MAX
- Dielectric Withstanding Voltage:
500 V AC AT Sea Level
- Insulation Resistance:
1000MEGA ohms MIN

Mechanical:

- Connector Mate and Unmate Force
Mate force:3.75kgf(MAX)
Unmate force:1.02kgf(MIN)
- Terminal Retention
1.2kgf(MIN)

Material:

- Housing:
High Temperature Thermoplastics,
U1 94V-0 PBT/LCP White/Black
- Contact:Copper Alloy C2680
- Shell: Copper Alloy C2680/SPCC

Finish:

- Contact: Plated Gold in Mating Area;
Tin On Solder Tails
- Shell:
Nickel Plating

UNITS	SCALE	东莞市田都电子有限公司 DONGGUAN TIANDU ELECTRONIC CO.,LTD TEL:0769-8538 4807 FAX:0769-8538 4842			
MM	1:1	DR.	TITLE: MICRO USB 5P B型 两脚DIP沉板1.0无卷边		
GENERAL TOLERANCE X ±0.30 X.X ±0.20 X.XX ±0.10 X° ±3° X.X° ±2°		MC	MAT'L:		DWG NO: CMTD03MC-10-2
		CHK.	DATE: 2011.06.28		MODEL NO. T10-05CB08
		APPD. CMTD	P	SIZE A4	

1

2

3

4

5

6