



- Note:
- Material:
    - Housing: High temperature thermoplastic with g.f,UL94v-0
    - Contact: copper alloy,t=0.20mm
    - Shell: copper alloy,t=0.25mm
  - Specification:
    - Current rating: 1 A Max.
    - Dielectric withstanding voltage: 100 V(ac) for 1 min.
    - Contact resistance: 50 mW Max.
    - Insulation resistance: 100 MW Min.
    - Total mating force: 3.57 Kgf Max.
    - Total unmating force: 1.0 Kgf Min.0.81~2.05 Kgf Min.after 10000 insertion/extraction cycles
    - Temperature range: -30°C~80°C

RECOMMENDED PCB LAYOUT

THESE DIMENSIONS AND SPECIFICATIONS ARE THE PROPERTY OF DONGSHAN TIANDU ELECTRONICS CO.,LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF DONGSHAN TIANDU ELECTRONICS CO., LTD

DIM	TOL	DIM	TOL
X.	±0.35 X°	±1°	
X.X	±0.25 X.X°	±0.5°	
X.XX	±0.15 X.XX°		
X.XXX	±0.10 X.XXX°		

UNITS mm	NAME (INTENDED USE) 通用
MAT'L 材质	MODEL NO. T10-05FB06
FINISH 镀层	APPD:
Q'TY 数量	CHKD:
	DR: <b>NO 2013.07.08</b>

<b>东莞市田都电子有限公司</b> DONGSHAN TIANDU ELECTRONICS CO., LTD			
TITLE: 5PIN 05V D-TYPE 全密封型 4P孔 0-1.0mm间距			
DRG NO.: CMTD03-75-009-03			
角法 FWJ:	SCALE 1/1	SHEET 页号	REV. 版本