







CAD FILE:



CIRCUIT DIAGRAM

MODEL NO.	L(mm)
T6-8080M-L	3.65
	4.35
	6.25
	8.4
	12.4



P.C.B. LAND PATTERN

SPECIFICATIONS

Rating	50mA 12V DC
Travel	0.25±0.1mm
Contact Resistance	≤ 100 mΩ
Operating temperature	-20℃ ~ 70℃(45% ~ 85% RH)
Operating Force	250±70gf
Operating Life	100,000 Cycles
Ip Rating	IP67

8					TOLERANCE UNLESS SPECIFIED WITHIN 1.5mm : ±0.1mm OVER 1.5mm : ±0.2mm	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DONGGUAN TIANDU ELECTRONICS CO.,LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF DONGGUAN TIANDU ELECTRONICS CO., LTD					
7											
6	KNOB	NYLON	1	RED							
5	COVER	BRASS	1	TIN PLATED							
4	WATERPROOF SILICONE	SILICA GEL	1	BLACK			DESCRIPTIONS OF REVISION				
3	TERMINAL	COPPER	2	PLATING SILVER	TITLE : WATERPROOF SWITCH		UNIT : mm		DRWG NO.: CMTDDZ-T6-8080M-00		
2	CONTACT	F.Ag/SUS	1	PLATING SILVER	MODEL: T6-8080M-L		SCALE: 3:1		DWN.	ERIC	2013-6-17
1	BASE	NYLON	1	BLACK	CMTDDZ 东莞市田都电子有限公司 DONGGUAN TIANDU ELECTRONICS CO.,LTD.				CHK'D	MAIKO	2013-6-17
NO.	PARTS	MATERIALS	Q'TY	FINISH					APPD.	Coco	2013-6-17

DESCRIPTIONS OF REVISION

APPD.