





CAD FILE:



MODEL NO.	KNOB(G/VG)
T2-163002-GX	(2~10)mm



SPECIFICATIONS	
Rating	0.3A 50V DC
CIRCUIT	1P6T
Timing	SHORTING
Travel	3.0mm
Contact Resistance	< 100 mΩ
Operating Force	250gf ± 100gf
Operating Life	10,000 cycles

NO.	PARTS	MATERIALS	Q'TY	FINISH
8				
7	STEEL BALL	STEEL	2	NATURAL
6	SPRING	STEEL WIRE	1	NATURAL
5	CONTACT CLIP	BRASS STRIP	1	Ag PLATED
4	TERMINAL	BRASS STRIP	7	Ag PLATED
3	BASE	PHENOLIC RESIN	1	NATURAL
2	FRAME	STEEL STRIP	1	NI PLATED
1	KNOB	POM	1	WHITE

<b>TOLERANCE</b> UNLESS SPECIFIED WITHIN 1.5mm : ±0.1mm OVER 1.5mm : ±0.2mm	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DONGGUAN TIANDU ELECTRONICS CO.,LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF DONGGUAN TIANDU ELECTRONICS CO., LTD		DESCRIPTIONS OF REVISION		APPD.
	<b>TITLE : HORIZONTAL SLIDE SWITCH</b>		UNIT : mm	DRWG NO.: CMTDDZ-T2-163002-00	
MODEL: T2-163002-GX		SCALE: 3:1	DWN. ERIC	2013-6-17	
<b>CMTDDZ 东莞市田都电子有限公司</b> DONGGUAN TIANDU ELECTRONICS CO.,LTD.		CHK'D MAIKO	2013-6-17		
		APPD. Coco	2013-6-17		