



SPECIFICATIONS:
 Contact current Rating:
 1.8 Amperes for pin1&pin4.
 0.25 Amperes other contacts
 Dielectric Withstanding Voltage:AC 100V(RMS)
 Insulation resistance:100Megohms Minimum.
 Contact Resistance:
 30mΩ Max for pin1&pin4
 50mΩ Max for other contacts
Mechanical Characteristics:
 Mating Force:35 Newtons.Maximum
 Unmating Force:10 Newtons.Mlimum.
MATERIAL: 8N Min After Durability
 Housing: PBT+30%GF 94V-0 COLOR:BLUE
 Contact: copper alloy(T=0.25mm)
 Shell: SPCC
PLATING:
 Contact: Au Plated on contact area
 Tin Plated on solder area
 Nickel underplating over all
 Shell: Nickel Plated
 operating Temperature:-55~+85°

料号备注

T10	3	M	013	S	XX	P	XX	XX	XX
-----	---	---	-----	---	----	---	----	----	----

12-半金雾锡1U*	00-胶壳后盖PBT蓝 前后壳电镀	
13-半金雾锡3U*	01-胶壳PBT蓝 后盖LCP黑 前后壳电镀	
14-半金雾锡5U*	02-胶壳后盖PBT蓝 前后壳镀金	R=ROHS2.0标准
15-半金雾锡15U*	03-胶壳后盖PBT蓝 前壳镀金 后壳电镀	V=无卤+ROHS2.0
16-半金雾锡30U*	04-胶壳PBT黑后盖PBT蓝 前后壳电镀	H=REACH标准
		D=透雾24H
		C=透雾48H

东莞市田都电子有限公司
 Dong Guan TianDu Electronics Co.,Ltd

UNLESS OTHERWISE SPECIFIED TOLERANCES	METRIC	APPROVAL	日期	品名规格	USB 3.0 BM焊线三件套(OD=6.0)	
	X. +/-	0.35	制图 WEIMINGJUN	2012.01.02		
	.X +/-	0.25	审核 WEIMINGJUN	2012.01.02	料号	SEE TABLE
	.XX +/-	0.25	核准 WEIMINGJUN	2012.01.02	文件位置	
FRACTIONS +/-		ANGLE OF PROJECTION		字张	工程图号:	
ANGLES +/-	2.00'			A4	DWG-USBBM-0101	
DIMENSIONS				版本	A4	
(METRIC)	(MM)			比例	1 : 1 状态码 A 页数 1 OF 1	