


P.C.B MOUNTING PATTERN  
BOTTOM VIEW

CMTDDZ

**OPERATING MODEL:**

SELF-LOCK:T5-70F022D-L  
Non-LOCK:T5-70F022D-NL



SCHEMATIC

SPECIFICATIONS	
Rating	0.1A 30V DC
CIRCUIT	2P-2T
Timing	NON-SHORTING
Travel	FULL:2.0mm
	LOCK:1.0mm
Operating Force	230gf ± 50gf
Operating Life	10,000 cycles

NO.	PARTS	MATERIALS	Q'TY	FINISH	TOLERANCE UNLESS SPECIFIED WITHIN 1.5mm : ±0.1mm OVER 1.5mm : ±0.2mm	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DONGGUAN TIANDU ELECTRONICS CO.,LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF DONGGUAN TIANDU ELECTRONICS CO., LTD	DESCRIPTIONS OF REVISION	APPD.	
8									
7	CAM STICK	SUS	1	NATURAL					
6	SPRING	SUS	1	NATURAL					
5	CONTACT CLIP	PHOSPHOR BRONZE	2	Ag PLATED					
4	TERMINAL	BRASS	6	Ag PLATED					
3	CASE	PA66	1	WHITE					
2	COVER	PA66	1	BLACK					
1	KNOB	POM	1	GREEN					
					<b>TITLE : VERTICAL SLIDE SWITCH</b>	<b>UNIT : mm</b>	<b>DRWG NO.: CMTDDZ-T5-70F022D-00</b>		
					<b>MODEL: SEE TABLE</b>	<b>SCALE: 3:1</b>	<b>DWN.</b>	<b>ERIC</b>	<b>2013-6-17</b>
					<b>CMTDDZ 东莞市田都电子有限公司</b>		<b>CHK'D</b>	<b>MAIKO</b>	<b>2013-6-17</b>
					<b>DONGGUAN TIANDU ELECTRONICS CO.,LTD.</b>		<b>APPD.</b>	<b>Coco</b>	<b>2013-6-17</b>