



CAD FILE:



OPERATING MODEL:

SELF-LOCK:T5-70F028D-L

Non-LOCK:T5-70F028D-NL



SPECIFICATIONS	
Rating	0.2A 12V DC
CIRCUIT	2C-2P
Timing	NON-SHORTING
Travel	FULL:1.9mm
	LOCK:1.1mm
Operating Force	250gf ± 100gf
Operating Life	10,000 cycles

NO.	PARTS	MATERIALS	Q'TY	FINISH	TOLERANCE	DESCRIPTIONS OF REVISION	APPD.
8					TOLERANCE UNLESS SPECIFIED WITHIN 1.5mm : ±0.1mm OVER 1.5mm : ±0.2mm	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DONGGUAN TIANDU ELECTRONICS CO.,LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF DONGGUAN TIANDU ELECTRONICS CO., LTD	
7	CAM STICK	SUS	1	NATURAL			
6	SPRING	SUS	1	NATURAL			
5	CONTACT CLIP	PHOSPHOR BRONZE	2	Ag PLATED			
4	TERMINAL	BRASS	6	Ag PLATED			
3	CASE	PA66	1	GREY	TITLE : VERTICAL SLIDE SWITCH	UNIT : mm	DRWG NO.: CMTDDZ-T5-70F028D-00
2	COVER	POM	1	BLACK	MODEL: SEE TABLE	SCALE: 3:1	DWN. ERIC 2013-6-17
1	KNOB	POM	1	WHITE	CMTDDZ 东莞市田都电子有限公司 DONGGUAN TIANDU ELECTRONICS CO.,LTD.	CHK'D	MAIKO 2013-6-17
						APPD.	Coco 2013-6-17