



<b>Rating</b>	1A 125VAC	<b>Electrical Life</b>	6,000 cycles
<b>Contact Resistance</b>	500mΩ Max	<b>Mechanical Life</b>	1,000,000 cycles
<b>Insulation Resistance</b>	>100MΩ DC500V	<b>Ambient Temper. Used</b>	-25℃ to +85℃
<b>Withstand Voltage</b>	AC500V 1min.	<b>Ambient Humidity Used</b>	≤85% at +40℃
<b>Soldering Temper.</b>	235±5℃ 5s	<b>Operating Force</b>	110±30gf max

6	端子	3	C2680	镀镍
5	触点	1	镀镍合金	
4	接板	1	PBT 阻燃料	
3	弹片	1	C17800	
2	盖片	1	PBT 阻燃料	
1	底座	1	PBT 阻燃料	
序号	零件名称	数量	材质	备注

制图 DRAWN	DAVID				东莞市田都科技有限公司 DONG GUAN SHI TIANDU TECHNOLOGY CO., LTD				
设计 DESIGN	ERIC				微动开关				
审核 CHECKED	JEFF		比例 SCALE	4:1	名称 TITLE	DM-OOP-110-3			
批准 APPROVE			张数 SHEET	1/1	料号 P/N NO.				
一般公差		±0.20	单位 UNIT	mm	模具编号 P/N NO.				
		±0.15	角度 ANGLES	±2.0°	纸套 SIZE	A4	角注 PROJ.		工程图 ENG DRAW
		±0.05							

版本 REV.	ECN 编号 ECN NO.	日期 DATE	变更内容 MODIFICATION	修改 DRAW	批准 APPROVE	TOLERANCE			
------------	-------------------	------------	----------------------	------------	---------------	-----------	--	--	--