

项目 Mapx	变更内容 Modification	日期 Date	修改人 Draw	核准 Approve

规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating
3.0A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)
2. 端子保持力: Terminal Retention
1.0kgf(MIN)

原材料: Material:

1. 塑胶: Housing:
Hing Temperature Ternmaplastics,
2. 端子: Contact: Copper Alloy C2680
3. 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

1. 端子: Contact: Plated Gold in Mating Area;
端子四周镀30-50U"(MIN) 镀底, 80-120U" 锡, 刷金1U"
2. 外壳: Shell:

铁壳四周镀80U"(MIN) 铜底, 80u' 锡, 铜壳镀80u' 锡

Nickel Plating

成品图 MANUFACTURE DWG		CMTDDZ 东莞市田都科技有限公司			
公差一览表 TOLERANCE UNLESS OTHERWISE		DONGGUAN TIANDU TECHNOLOGY CO.,LTD.			
.X±0.20	X.±5'	日期 DATE	2016.10.20	单位 UNIT	MM
.XX±0.10	.X±2'	审核 CHECKED		制图 DRAWING	
.XXX±0.05	.XX±1'	核准 APPROVE		DWG NO.	T10-2F137H-K-W
				品名 NAME	90度卷边弯脚插座
				版本 VER	
				页码 SHEET	

