



1. Material:

Contacts: Phosphor Bronze

Insulator: PBT+30%

G. F. UL 94V-0

Shell: SPCC

2. Mechanical:

Mating: 35N max.

Withdrawal Force: 10N min.

Durability: 1500 cycles min.

3. Electrical:

Current max (amps) 1.5A

Voltage max (volts) 30V

Withstanding Voltage 750V AC

Contact Resistance (ohms) 30

milliohms max insulation

Resistance (ohms) 1000 Megohms min.

4. Plating:

Contacts: Gold And Tin Over

Nickel Plated

Shell: Nickel over all plating.

5. Environmental:

Temperature Range: -55 to 85

产品图
MANUFACTURE DWG

公差一览表
TOLERANCE UNLESS OTHERWISE

CMTDDZ 东莞市田都科技有限公司
Dongguan TianDu Technology Co. Ltd.

单位 UNITS	MM		INCH
.X	±0.20	.X	±---
.XX	±0.10	.XX	±----
.XXX	±0.05	.XXX	±-----

2013. 08. 29

产品名称		USB A/F 双层90度卷边弯脚			
角法 VIEW	制图 DRAWING	审核 CHKD	ERIC		
比例 SCALE	设计 DESIGN	核准 APPD			
版本 REV	图号	T10-2F176-01	张数 1/1		