



RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm

备注:

1.材质:

1.1胶芯: LCP+30%G.F UL94V-0

1.2端子: 磷铜, T=0.12mm; 镀底, 镀金1μ”

1.3外壳: 不锈钢, T=0.30mm; 表面镀镍100μ”
或亮锡100μ”

2.主要特性:

2.1额定电流: 0.5A

2.2接触阻抗: 30mΩ MAX

2.3绝缘阻抗: 100MΩ MIN 250V DC

2.4耐压测试: 250V AC

2.5沾锡性: 温度250±5℃, 时间5±0.5s

2.6整体插入力: 3.57kgf MAX

整体拔出力: 1.02kgf MIN

2.7使用寿命: 10000次

2.8工作温度: -30℃~+80℃

A1	GND	B12	GND
A2		B11	
A3		B10	
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10		B3	
A11		B2	
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

公差尺寸表 Tolerance		产品名称 Product Name	USB Type-C/F 16PIN 6.5夹板(壳无焊脚)		产品型号 Part NO.	T11-16JB**6.5H-01	
		产品规格 Product Standard	16PIN 夹板0.6板/0.8板/1.0板 H=6.5		图号 Drawing NO.		
±0.50 X° ±	制 图	审 核	批 准	产品工程图	图纸比例	FIT	A4
±0.30 X° ±	ERIC	JEFF		模具编号 Mold NO.	TD5098	共1页	第1页
.XX ±0.10 .XX° ±	日期/Date	日期/Date	日期/Date	CMTDDZ 东莞市田都科技有限公司 Dongguan TianDu Technology Co., Ltd.			
.XXX ±0.05	2019-05-09	2019-05-09					