



NOTES:

1. Material:

- 1.1:主体:LCP
- 1.2:护套:LCP
- 1.3:钢壳:SUS201, T=0.20±0.02mm.
- 1.4:卡钩:SUS301, T=0.40±0.05mm.
- 1.5:端子:C2680, T=0.20±0.02mm

2. Finish:

- 2.1 端子:Test point: Ni 50u"/Au 1u" MIN.
Soldering area: Ni 50u"/Tin (PB Free) 100u" MIN.
The other area: Ni 50u" MIN.
- 2.2 钢壳: Ni 60u" MIN.
- 2.3 盐雾测试: 48H

3. Specification:

- 3.1: Rating:
Rated voltage: AC 100V. Rated current: 1A.
- 3.2: Electrical:
Contact resistance:
30mΩ MAX. at 20mV MAX, 50mA.
Insulation resistance:
50MΩ MIN. at 500V DC for 1Minute.
Dielectric withstanding voltang:
No discharge, flashover or breakdown
at 500V/AC 1Minute.

3.3: MECHANICAL:

- INSERTION FORCE: 35N Max.
- EXTRACTION FORCE: 8N Min.
- DURABILITY: 3000 Cycles .

CMTDDZ 东莞市田都科技有限公司
Dongguan TianDu Technology Co. Ltd.

					General X±0.25	Angle X'±3'	设计 DESIGN		
					.X±0.20	.X'±2'	校阅 CHECK		
					.XX±0.15	.XX'±1'	承认 APPRO.		
					.XXX±0.08				
工程变更通知单号 ECN NO.	AO	说明 DESCRIPTION	NEW	改变 CHANGE	日期 DATE	2020. 10. 13	GENERAL TOLERANCE UNLESS OTHERWISE NOTED		

名称 TITLE:	Micro 5P 单排7.2/前5后 2(2/3短路/不通槽)		
料号 PART NO.	T10-2MK-003S		
SCALE	1:1	UNIT:mm	A4 □ SHEET: 1 of 1