


RECOMMENDED PCB LAYOUT
TOLERANCE: ±0.05



A5	CC1	B5	CC2
A9	VBUS	B9	VBUS
A12	GND	B12	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

NOTES:

SPECIFICATION:

1. CURRENT RATING: 3A MAX
2. VOLTAGE: 100 VAC
3. TEMPERATURE RANGE: -25 °C ~ 85 °C
4. CONTACT RESISTANCE: 40 MILLIONHM MAX
5. INSULATION RESISTANCE: 100 MEGOHMS MIN.
6. INSERTION FORCE : 5N~20N
7. UNMATING FORCE: 8N~20N
8. DURABILITY: 5000 CYCLES

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	CMTDDZ 东莞市田都科技有限公司 Dongguan TianDu Technology Co. Ltd.	
X. ±0.35	X' ±2.0'	ERIC	2020/11/12		
.X ±0.25	.X' ±1.0'	CHECK	DATE	FILE NAME (品名)	TYPE-C 6PIN 沉插1.6 L6.5 铜夹片
.XX ±0.15	.XX' ±0.5'	APPRO.	DATE	PART NO (料号)	T11-06CB15-6.5L
.XXX ±0.10				DRAWING NO (图号)	
UNIT:mm	SCALE 1:1				REV. A0
A4	SHEET: 1 of 1				