




REV.	ECN	DESCRIPTION	MDF'D	DATE
		新订图面		



备注 (NOTE):

1. 材质:

- 1.1 胶芯: LCP UL94 V-0
- 1.2 端子: C2680, T=0.2mm; 镍底, 镀金
- 1.3 外壳: 不锈钢201-H 表面镀镍

2. 电气特性:

- 2.1 接触区: 接触电阻40mΩ Max, 允许10mΩ变化量. 测试条件: 20mv, 100mA下测量.
- 2.2 接触电流: 3A VBUS引脚; 1.25A用于GND引脚; 其他引脚为0.25A.

2.3 额定电压: 5V.




2.4 耐电压: 100VAC.

2.5 绝缘电阻: 至少100兆欧.

3. 机械性能:

- 3.1 插入力: 0.5-2.0Kg
- 3.2 拔出力: 0.6-2.04Kg
- 3.3 插拔次数: 5000次.
- 4. 工作环境: -20℃ to +85℃.

CMTDDZ



USB TYPE C PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME	PIN NUMBER	SIGNAL NAME
		B12	GND
		B9	VBUS
A5	CC1		
		B5	CC2
A9	VBUS		
A12	GND		

TABLE:

NO	PART	Q'TY	Material
1	SHELL	1	ZINC ALLOY, NI30u"Min PLATED
2	CONTACT	6	C2680, TIN80u"/Au1u"/NI30u" PLATED
3	1MD HOUSING	1	LCP UL94 V-0 BLACK
4	CAP	1	LCP UL94 V-0 BLACK
5	WATERPROOF RING	1	SILICONE UL94 V-0 BLACK

CMTDDZ 东莞市田都科技有限公司 Dongguan TianDu Technology Co. Ltd.		页码 (SHEET)	1	单位 (UNIT):	MM
		版本 (REV)	A1	比例 (SCALE)	1:1
品名 (ITEM NO)	TYPE-C2P焊线式8.6	日期 (DATE)	2022.7.6	未注公差 TOLERANCE UNDESCRIPTED I.I ±0.20 I.II ±0.15 I.III ±0.10 I.IV ±0.05 I.V ±0.02	
料号 (PART NO)	T11-04HF-05-6.6-8.6	设计 (DESIGN)	ERIC		
图号 (DWG NO)	A1	审核 (CHECKED)			
		核准 (APPROVED)			
These drawings and specifications are Dongguan TianDu Technology Co. Ltd. The property should not be copied. Without Dongguan TianDu Technology Co. Ltd. Prior written consent to copy or use in any way					